



FKD

Mancal em inox SF



Caixa	Eixo		Dimensão nominal (mm)									Paraf.	Peso (kg)		D	Rolamento SUC 200	
	Ø pol	Ø mm	a	e	i	g	l	s	t	Ze	SUCSF2		z	Bi			
SF 204 ⁽¹⁾	3/4	20	86,0	64	15,0	12,0	25,5	12	2	47	M10 3/8	0,60	47,0	33,3	31,0		
SF 205 ⁽¹⁾	1	25	94,5	70	16,0	14,0	27,0	12	2	54	M10 3/8	0,80	52,0	35,8	34,1		
SF 206 ⁽¹⁾	1-1/8 1-3/16 1-1/4	30	107,0	83	18,0	14,0	31,0	12	2	62	M10 3/8	1,10	62,0	40,2	38,1		
SF 207 ⁽¹⁾	1-1/4 1-7/16	35	117,0	92	19,0	14,3	34,0	14	3	65	M12 1/2	1,50	72,0	44,4	42,9		
SF 208 ⁽¹⁾	1-1/2	40	130,0	102	21,0	14,3	36,0	16	3	71	M14 1/2	1,90	80,0	51,2	49,2		
SF 209 ⁽¹⁾	1-11/16 1-3/4	45	136,0	105	22,0	14,3	38,0	16	3	71	M14 1/2	2,00	85,0	52,2	49,2		
SF 210 ⁽¹⁾	2	50	142,0	111	22,0	15,1	40,0	16	3	75	M14 1/2	2,40	90,0	54,6	51,6		
SF 211 ⁽¹⁾	2 2-3/16	55	161,0	130	25,0	18,0	43,0	19	4	82	M16 5/8	3,60	100,0	58,4	55,6		
SF 212 ⁽¹⁾	2-7/16	60	174,0	143	29,0	18,0	48,0	19	4	90	M16 5/8	4,10	110,0	68,7	65,1		
SF 213		65	187,0	149	30,0	22,0	50,0	19	4	98	M16 5/8	5,50	120,0	69,7	65,1		
SF 214		70	193,0	152	31,0	22,0	54,0	19	4	100	M16 5/8	6,80	125,0	75,4	74,6		
SF 215	3	75	200,0	159	34,0	22,0	56,0	19	4	109	M16 5/8	6,80	130,0	78,5	77,8		
SF 216	3-3/16	80	208,0	165	34,0	23,0	58,0	23	4	111	M20 3/4	8,60	140,0	83,3	82,6		
SF 217	3-7/16	85	227,0	175	36,0	23,0	63,0	23	5	110	M20 3/4	9,90	150,0	87,6	85,7		
SF 218		90	235,0	187	40,0	23,0	68,0	23	5	115	M20 3/4	12,20	160,0	96,3	96,0		