



Mancal em inox SP



Caixa	Eixo		Dimensão nominal (mm)										Paraf.	Peso (kg)		D	Rolamento	
	Ø pol	Ø mm	h	a	e	b	s1	s2	g	w	t	Ze		SUCSP2			Bi	m
SP 204 ⁽¹⁾	3/4	20	33,3	126,0	95	38,0	13	19	15	65	2	66	M10 3/8	0,90		47,0	31,0	18,3
SP 205 ⁽¹⁾	1	25	36,5	138,0	105	37,0	13	19	16	70	2	77	M10 3/8	1,00		52,0	34,1	19,8
SP 206 ⁽¹⁾	1-1/8 1-3/16 1-1/4	30	42,9	163,0	121	47,0	17	21	18	83	2	89	M14 1/2	1,40		62,0	38,1	22,2
SP 207 ⁽¹⁾	1-1/4 1-7/16	35	47,6	165,0	127	47,0	17	21	19	94	3	90	M14 1/2	1,90		72,0	42,9	25,4
SP 208 ⁽¹⁾	1-1/2	40	49,2	183,0	137	53,5	17	23	19	100	3	101	M14 1/2	2,20		80,0	49,2	30,2
SP 209 ⁽¹⁾	1-11/16 1-3/4	45	54,0	188,5	146	53,5	17	23	20	109	3	98	M14 1/2	2,50		85,0	49,2	30,2
SP 210 ⁽¹⁾	2	50	57,2	203,5	159	59,0	20	25	22	114	3	103	M16 5/8	3,10		90,0	51,6	32,6
SP 211 ⁽¹⁾	2 2-3/16	55	63,5	217,5	171	59,0	20	25	22	125	4	111	M16 5/8	4,00		100,0	55,6	33,4
SP 212 ⁽¹⁾	2-7/16	60	69,8	239,0	184	69,0	20	25	25	138	4	119	M16 5/8	5,40		110,0	65,1	39,7
SP 213		65	76,2	265,0	203	70,0	25	29	27	150	4	132	M20 3/4	6,60		120,0	65,1	39,7
SP 214		70	79,4	266,0	210	74,0	25	31	28	158	4	130	M20 3/4	7,40		125,0	74,6	44,4
SP 215	3	75	82,6	275,0	217	74,0	25	31	28	163	4	144	M20 3/4	8,00		130,0	77,8	44,5
SP 216	3-3/16	80	88,9	292,0	232	78,0	25	31	30	175	4	147	M20 3/4	9,50		140,0	82,6	49,3
SP 217	3-7/16	85	95,2	310,0	247	84,0	25	31	32	187	5	137	M20 3/4	10,70		150,0	85,7	51,6
SP 218		90	101,6	327,0	262	86,0	27	33	34	200	5	139	M22 7/8	14,30		160,0	96,0	56,3